

**Cisco Configuration Management System**

Host Name: Catalyst-3750

Enable SNMP

Enable Traps

**Types of traps to send:**

- Send all traps
- bgp
- enable
- ipmulticast
- rtr
- vlan-membership
- copy-config
- config
- fru-ctrl

CNA

**eXpresso - Microsoft Internet Explorer**

Address: http://ue-apps/Common%20UI%20Client%20Project%20Team/

**Catalyst 3750 Series Device Manager**

Admin - Logout

Uptime: 2 weeks, 1 day, 2 hours, 10 minutes

Next refresh in 47 seconds

MODE: STATUS

PORT STATUS: LINK UP, LINK DOWN, PORT DOWNLED, ADMIN DOWNLED, LINK FAULT, SYSTEM LED, SWITCH HEALTH, SWITCH FAULT

eXpresso

**Cisco SMB Support Assistant**

Port	Description	Enabled	Speed
1		●	100
2	auto	●	auto
3		●	auto
4		●	auto
5		●	auto
6		●	auto
7		●	auto
8		●	auto
9		●	auto
10		●	auto
11		●	auto
12		●	auto
13		●	100
14		●	auto
15		●	100
16		●	auto
17		●	auto

PLEASE NOTE: The device information contained within this page, devices added through the client are available only in the portal's Device Manager.

SMB SA

**SecurityDevice Management**

Home | Configure | Monitor | Print | Refresh | Help

**Interfaces and Connections**

Create New Connections | Edit Existing Connections

Interface	IP	Type	Slot	Status	Description
Dialer1	No IP Address	Dialer		Up	
Ethernet0	No IP Address	Ethernet		Up	
FastEthernet0	171.71.220.80	10/100/Ethernet		Up	

SDM 2.1

**Cisco 1100 Access Point**

Hostname: AP1121

AP1121 uptime is 6 weeks, 3 days, 19 hours, 26 minutes

**Configuration**

Software Status	Enabled	Hardware Status	Up
Operational Rates	1, 2, 5.5, 6 MB/sec	Basic Rate	1.0MB/sec
Aironet Extensions	Enabled	Carrier Set	Americas
Current Radio Channel	2422 MHz Channel 3	Transmitter Power CCK/OFDM	100 mW/30 mW
Role in Network	Access Point / Root		

**Interface Statistics**

Receive	Transmit
5 Min Input Rate (bits/sec)	5 Min Output Rate (bits/sec)
0	0
5 Min Input Rate (packets/sec)	5 Min Output Rate (packets/sec)
0	0
Time Since Last Input	Time Since Last Output
6w3d	1d18h
Total Packets Input	Total Packets Output
3105	128366
Total Bytes Input	Total Bytes Output
24926	11608950

**Error Statistics**

Receive	Transmit
Total Input Errors	Total Output Errors
0	43
Throttles	Last Output Hang
0	never

AccessPoint